
Gf-Patterns V 1.9

GF By  @TomNomNom

A wrapper around grep, to help you grep for things

installation

Go Path Setup

If you've got Go installed and configured you can install [waybackurls](#) & [Gf](#) with:

```
1 ►  
2  
3 go get -u github.com/tomnomnom/waybackurls
```

```
1 ►  
2 go get -u github.com/tomnomnom/gf
```

If you've installed using `go get`, you can enable auto-completion to your `.bashrc` like this:

```
1 ►  
2 echo 'source $GOPATH/src/github.com/tomnomnom/gf/gf-completion.bash'  
   >> ~/.bashrc
```

Note that you'll have to restart your terminal, or run `source ~/.bashrc` for the changes to take effect.

To get started quickly, you can copy the example pattern files to `~/ .gf` like this:

```
1 ►  
2 mkdir .gf
```

```
1 ►  
2 cp -r $GOPATH/src/github.com/tomnomnom/gf/examples ~/.gf
```

MY Gf Patterns installation

```
1 ►  
2 git clone https://github.com/1ndianl33t/Gf-Patterns
```

To get started quickly, you can copy the example pattern files to `~/ .gf` like this:

```
1 ►  
2 mkdir .gf
```

```
1 ►
2 mv ~/Gf-Patterns/*.json ~/.gf
```

Use example

```
1 ►
2
3 cat subdomains.txt | waybackurls | sort -u >> waybackdata | gf ssrf |
  tee -a ssfrparams.txt►
4
5 cat waybackdata | gf redirect | tee -a redirect.txt
```

Pattern Files

The pattern definitions are stored in `~/.gf` as little JSON files that can be kept under version control:

gf ssrf

```
1 ►
2 cat ~/.gf/ssrf.json
3
4 {
5     "flags": "-iE",
6     "patterns": [
7
8         "access",
9         "admin",
10        "dbg",
11        "debug",
12        "edit",
13        "grant",
14        "test",
15        "alter",
16        "clone",
17        "create",
18        "delete",
19        "disable",
20        "enable",
21        "exec",
22        "execute",
23        "load",
24        "make",
25        "modify",
26        "rename",
27        "reset",
28        "shell",
29        "toggle",
```

```
30     "adm",
31     "root",
32     "cfg",
33     "dest",
34     "redirect",
35     "uri",
36     "path",
37     "continue",
38     "url",
39     "window",
40     "next",
41     "data",
42     "reference",
43     "site",
44     "html",
45     "val",
46     "validate",
47     "domain",
48     "callback",
49     "return",
50     "page",
51     "feed",
52     "host",
53     "port",
54     "to",
55     "out",
56     "view",
57     "dir",
58     "show",
59     "navigation",
60     "open"
61
62 ]
63 }
```

gf redirect

```
1  ►
2  cat ~/.gf/redirect
3
4  {
5      "flags": "-iE",
6      "patterns": [
7  "forward=",
8  "dest=",
9  "redirect=",
10 "uri=",
11 "path=",
12 "continue=",
13 "url=",
14 "window=",
```

```
15 "to=",
16 "out=",
17 "view=",
18 "dir=",
19 "show=",
20 "navigation=",
21 "Open=",
22 "file=",
23 "val=",
24 "validate=",
25 "domain=",
26 "callback=",
27 "return=",
28 "page=",
29 "feed=",
30 "host=",
31 "port=",
32 "next=",
33 "data=",
34 "reference=",
35 "site=",
36 "html="
37 ]
38 }
```

gf rce

```
1 ►
2 cat ~/.gf/rce.json
3 {
4     "flags": "-iE",
5     "patterns": [
6
7         "daemon",
8         "upload",
9         "dir",
10        "execute",
11        "download",
12        "log",
13        "ip",
14        "cli",
15        "cmd"
16    ]
17 }
```

Gf idor

```
1 ►
2 cat ~/.gf/idor.json
3 {
4     "flags": "-iE",
```

```
5     "patterns": [  
6  
7     "id",  
8     "user",  
9     "account",  
10    "number",  
11    "order",  
12    "no",  
13    "doc",  
14    "key",  
15    "email",  
16    "group",  
17    "profile",  
18    "edit",  
19    "report"  
20  
21 ]  
22 }
```

Gf Sqli

```
1  ►  
2  cat ~/.gf/sqli.json  
3  {  
4      "flags": "-iE",  
5      "patterns": [  
6  
7          "id",  
8          "select",  
9          "report",  
10         "role",  
11         "update",  
12         "query",  
13         "user",  
14         "name",  
15         "sort",  
16         "where",  
17         "search",  
18         "params",  
19         "process",  
20         "row",  
21         "view",  
22         "table",  
23         "from",  
24         "sel",  
25         "results",  
26         "sleep",  
27         "fetch",  
28         "order",  
29         "keyword",  
30         "column",
```

```
31     "field",
32     "delete",
33     "string",
34     "number",
35     "filter"
36 ]
37 }
```

Gf LFI

```
1  ►
2  cat ~/.gf/lfi.json
3  {
4      "flags": "-iE",
5      "patterns": [
6
7          "file",
8          "document",
9          "folder",
10         "root",
11         "path",
12         "pg",
13         "style",
14         "pdf",
15         "template",
16         "php_path",
17         "doc"
18     ]
19 }
```

Gf ssti

```
1  ►
2  cat ~/.gf/ssti.json
3
4
5  {
6      "flags": "-iE",
7      "patterns": [
8
9          "template",
10         "preview",
11         "id",
12         "view",
13         "activity",
14         "name",
15         "content",
16         "redirect"
17     ]
18 }
```

Gf debug_logic

```
1 ►
2 cat ~/.gf/debug_logic.json
3 {
4     "flags": "-iE",
5     "patterns": [
6
7         "access",
8         "admin",
9         "dbg",
10        "debug",
11        "edit",
12        "grant",
13        "test",
14        "alter",
15        "clone",
16        "create",
17        "delete",
18        "disable",
19        "enable",
20        "exec",
21        "execute",
22        "load",
23        "make",
24        "modify",
25        "rename",
26        "reset",
27        "shell",
28        "toggle",
29        "adm",
30        "root",
31        "cfg",
32        "config"
33    ]
34 }
```

Donations

You can encourage me to contribute more to the open source with donations.

- Paypal - <https://www.paypal.me/1ndianl33t>
- GooglePay, Paytm -

8085778875

Credit

  Bugcrowd HUNT  

Contributors

@victoni added more redirect parameters

@s0meguy1 redirect & ssrf pattern Added additional filters

Contact

 